
PAC-VAC® & STEALTH-VAC

PAC-VAC®

The PAC-VAC® is battery operated and self-contained, runs up to eight hours continuously on one 9 volt alkaline battery. This versatile unit can be clipped to your belt or pocket for one-handed portable operation. The PAC-VAC® is constructed with ESD safe materials and comes complete with the following features:

- . Bright blue power on LED indicator light.
- · A belt/pocket clip on the housing.
- 5 feet of coiled vacuum hose, VCH-1/16-5.
- · A set of nine vacuum tips, VCS-9-B.
- V3200 PAC-VAC kit
- · A vacuum pick-up handle, VVP-200.
- . 9 volt disposable alkaline battery.
- · Lightweight only 156 grams.
- · Produces vacuum of up to 16 inches of mercury.

V3200-CLN PAC-VAC kit Clean room safe VCS-9-B Replacement probe/cup kit Refer to pages 14-15 for small parts tips





STEALTH-VACTM

The STEALTH-VAC operates directly on compressed air or nitrogen. Simply place the vacuum tip on the part to pick it up and tap the control button to release the part.

Pu		LU		Pic	
VV	S	V-	K	17	

The normally open Stealth Vac Kit with a set of 9 vacuum tips, 6 feet of 1/16" coiled vacuum hose, a set of nine ESD-Safe vacuum tips (VCS-9-B), a (V3014-1/8NPT) 1/8" NPT to 1/16" barb adapter for the supply line, the vacuum generating handle and a (VBM-3) holder for the wand. Operates off of 30 to 70 psi compressed air or nitrogen. This tool grips the part without depressing the button. A slight tap of the button releases

VVSV-X

The normally open Stealth Vac vacuum generating handle. Includes 6 feet of 1/16" coiled vacuum hose, a (V3014-1/8NPT) 1/8" NPT to 1/16" barb adapter for the supply line and the vacuum generating handle. Operates off of 30 to 70 psi compressed air or nitrogen. This tool grips the part without depressing the button. A slight tap of the button releases the part

STEALTH-VAC™ ELITE

The STEALTH-VAC operates directly on compressed air or nitrogen. Simply place the vacuum tip on the part to pick it up and press the control button to pick up the part and press the button again to release the part.

VVSV-NC-KIT

The normally closed Stealth Vac™ ELITE Kit with a set of 9 vacuum tips, 6 feet of 1/16" coiled vacuum hose, a set of nine ESD-Safe vacuum tips (VCS-9-B)a (V3014-1/8NPT) 1/8" NPT to 1/16" barb adapter for the supply line, the vacuum generating handle and a (VBM-3) holder for the wand. Operates off of 30 to 50 psi compressed air or nitrogen. This tool grips the part only while depressing the button. Releasing the button releases the part. Conserves factory air

VVSV-NC-X

The normally closed Stealth Vac ELITE vacuum generating handle. Includes 6 feet of 1/16" coiled vacuum hose, a (V3014-1/8NPT) 1/8" NPT to 1/16" barb adapter for the supply line and the vacuum generating handle. Operates off of 30 to 50 psi compressed air or nitrogen. This tool grips the part only while depressing the button. Releasing the button releases the part. Conserves factory air



The PAC-VAC is a portable continuous vacuum handling system that operates off a standard size 9 volt battery.



PAC-VAC







